

## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Material number : 000000000001047443

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation  
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

## SECTION 2. HAZARDS IDENTIFICATION

**Emergency Overview**

Appearance	Aerosol containing a compressed gas
Colour	red
Odour	solvent-like

**GHS Classification**

Flammable aerosols : Category 1  
 Gases under pressure : Compressed gas  
 Acute toxicity (Inhalation) : Category 4  
 Skin irritation : Category 2  
 Eye irritation : Category 2A  
 Carcinogenicity : Category 2  
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

**GHS Label element**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.

## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

## Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

P281 Use personal protective equipment as required.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

Dispose of contents/container in accordance with local regulation.

**Potential Health Effects****Carcinogenicity:**

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans naphthalene	91-20-3
<b>ACGIH</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
<b>NTP</b>	Reasonably anticipated to be a human carcinogen naphthalene	91-20-3

## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

## Hazardous components

Chemical Name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 30 - < 50
Fuel oil, no. 2	68476-30-2	>= 30 - < 50
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 20
carbon dioxide	124-38-9	>= 5 - < 10
4-Nonylphenol branched, ethoxylated	127087-87-0	>= 1 - < 5
naphthalene	91-20-3	>= 0.1 - < 1

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
Keep patient warm and at rest.  
If unconscious place in recovery position and seek medical advice.  
Keep respiratory tract clear.
- In case of skin contact : If skin irritation persists, call a physician.  
If on clothes, remove clothes.  
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Take victim immediately to hospital.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15**

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

---

Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling	:	Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
-------------------------	---	--

## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Oxidizing agents  
Do not store near acids.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m <sup>3</sup>	OSHA P0
naphthalene	91-20-3	STEL	30,000 ppm 54,000 mg/m <sup>3</sup>	OSHA P0
		TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m <sup>3</sup>	NIOSH REL
		ST	15 ppm 75 mg/m <sup>3</sup>	NIOSH REL
		TWA	10 ppm 50 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10 ppm	OSHA P0

## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

			50 mg/m <sup>3</sup>	
		STEL	15 ppm	OSHA P0
			75 mg/m <sup>3</sup>	

**Biological occupational exposure limits**

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

**Personal protective equipment**

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.  
In the case of dust or aerosol formation use respirator with an approved filter.
- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : Aerosol containing a compressed gas
- Colour : red
- Odour : solvent-like
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point : No data available
- Flash point :  
Not applicable
- Evaporation rate : No data available

**A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15**

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

---

Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Density	: 0.83 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 45.19 kJ/g

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Acids Strong oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Smoke

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : 1.51 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method

**A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15**

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

**Components:****acetone:**

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l  
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: &gt; 7,426 mg/kg

LD50 Rabbit: &gt; 7,426 mg/kg

**Distillates (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 Rat: &gt; 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l  
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: &gt; 2,000 mg/kg

**4-Nonylphenol branched, ethoxylated:**

Acute oral toxicity : LD50 Rat: 5,000 mg/kg

Acute dermal toxicity : LD50 Rabbit: 2,573 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation****Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**acetone:**



## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

Fuel oil, no. 2:  
 Distillates (petroleum), hydrotreated light:  
 carbon dioxide:  
 4-Nonylphenol branched, ethoxylated:  
 naphthalene:

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**Components:**

Distillates (petroleum), hydrotreated light:  
 Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**

Partition coefficient: n- : Remarks: No data available  
 octanol/water

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of  
 Stratospheric Ozone - CAA Section 602 Class I  
 Substances

Remarks

This product neither contains, nor was manufactured  
 with a Class I or Class II ODS as defined by the U.S.  
 Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

**A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15**

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

+ B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

**Components:**
**Distillates (petroleum), hydrotreated light :**

Additional ecological information : No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY
---

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity
--

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity
--

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity
--

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity
---

**SECTION 15. REGULATORY INFORMATION**
**EPCRA - Emergency Planning and Community Right-to-Know Act**

## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

## CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Sudden Release of Pressure Hazard  
Acute Health Hazard  
Chronic Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:  
naphthalene 91-20-3 0.1662 %

**California Prop 65** WARNING! This product contains a chemical known to the State of California to cause cancer.  
naphthalene 91-20-3

## The components of this product are reported in the following inventories:

**TSCA** On TSCA Inventory  
**DSL** All components of this product are on the Canadian DSL  
**AICS** On the inventory, or in compliance with the inventory  
**NZIoC** Not in compliance with the inventory  
**PICCS** On the inventory, or in compliance with the inventory  
**IECSC** On the inventory, or in compliance with the inventory

## Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECl (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

## SECTION 16. OTHER INFORMATION

## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15


Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

## Further information

## NFPA:



## HMIS III:

HEALTH	2*
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

## OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause  
drowsiness or dizziness. Suspected of causing cancer.

Precautionary statements

: **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear protective gloves. Use personal protective equipment as required.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.  
**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	03/04/2016
Print Date:	06/26/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

# SAFETY DATA SHEET



## A00376 ZEP AUTO ENGINE DEGR ZAA376 20N15

Version 1.1

Revision Date 03/04/2016

Print Date 06/26/2017

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.