

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Material number : 00000000001048255

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	black, green
Odour	solvent-like

GHS ClassificationFlammable aerosols : Category 1
Gases under pressure : Liquefied gas**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.**Storage:**

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

P403 Store in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 1 - < 5
acetone	67-64-1	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on clothes, remove clothes.
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
Rinse immediately with plenty of water for at least 15 minutes.
- If swallowed : Keep respiratory tract clear.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist. Always replace cap after use.
Conditions for safe storage	: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

or throw into fire even after use. Do not spray on flames or red-hot objects.

No smoking.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions.

Keep in a cool, well-ventilated place.

Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
		PEL	1,000 ppm 1,800 mg/m ³	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		TWA	800 ppm 1,900 mg/m ³	OSHA P0
		PEL	800 ppm 1,900 mg/m ³	CAL PEL
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
		STEL	750 ppm 1,780 mg/m ³	CAL PEL
		C	3,000 ppm	CAL PEL
PEL	500 ppm 1,200 mg/m ³	CAL PEL		

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

				shift (As soon as possible after exposure ceases)		
--	--	--	--	---	--	--

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Safety glasses

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : black, green

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : No data available

Flash point :
No data available

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

Relative vapour density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 46.08 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Hydrocarbons Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects****Carcinogenicity:**

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity**Components:****propane:**

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 658 mg/l
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

butane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product:**

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

SAFETY DATA SHEET



A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

No data available

Reproductive toxicity

No data available

propane:

butane:

Naphtha (petroleum), hydrotreated light:

acetone:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

butane :

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. The product should not be allowed to enter drains, water courses or the soil.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12

Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard
Fire Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

ethylbenzene	100-41-4
benzene	71-43-2
naphthalene	91-20-3

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

toluene	108-88-3
benzene	71-43-2

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

A00352 ZEP AUTO CHAIN LUBE ZAA352 16N12


Version 3.3

Revision Date 09/23/2016

Print Date 06/26/2017

Further information

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word

Hazard statements

Precautionary statements

: **Danger:**
: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
: **Prevention:** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.
Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.3
Revision Date:	09/23/2016
Print Date:	06/26/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.